

ET2831HP

208 VAC SINGLE PHASE



THREE CIRCUITS 26 AMPS EACH
EACH CIRCUIT MUST BE FUSED
AT SAFETY SHUTOFF BOX
PLACED NEAR KILN.

16060 WATTS

ET2831HP2P3CSA.DWG

WIRE DIRECT FROM FUSED
SAFETY CUTOFF SWITCH
NEAR KILN


INCOMING POWER 208 VAC
THREE SEPARATE FUSED CIRCUITS
26A, 26A, & 26A RESPECTIVELY

CUSTOMER CONNECTIONS




THREE POWER CIRCUITS
25 AMPS EACH

GROUND TO CASE

COMPLY WITH NATIONAL
ELECTRIC AND LOCAL
CODES FOR WIRE SIZE.



NOT FOR DISCONNECT
MARGUAT LIGHTED SWITCH



#10

#10

#10

#10

#10

#10

#10

#10

#10

#10

#10

#10

#10

#10

#10

#10

#10

#10

#10

#10

#10

#10

#10

#10

TDP 16 OHMS

16 OHMS

16 OHMS

16 OHMS

10.8 OHMS

5.7 OHMS HALF ELEMENT

5.7 OHMS HALF ELEMENT

10.8 OHMS

10.8 OHMS

16 OHMS

FRONT OF KILN
elements

CINCHE 5-303AB